




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>H01L</b>	<b>A2</b>	(11) International Publication Number: <b>WO 00/33355</b> (43) International Publication Date: 8 June 2000 (08.06.00)
(21) International Application Number: PCT/US99/28086 (22) International Filing Date: 23 November 1999 (23.11.99) (30) Priority Data: 09/201,737 1 December 1998 (01.12.98) US (71) Applicant: APPLIED MATERIALS, INC. [US/US]; 3050 Bowers Avenue, Santa Clara, CA 95052 (US). (72) Inventors: PERLOV, Ilya; 183 Plake Avenue, Santa Clara, CA 95051 (US). GANTVARG, Evgueni; 2679 Forbes Avenue, Santa Clara, CA 95051 (US). BELITSKY, Victor; 1618 Meadowlark Lane, Sunnyvale, CA 94087 (US). (74) Agents: BERNADICOU, Michael, A. et al.; Blakely, Sokoloff, Taylor & Zafman LLP, 7th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025 (US).		(81) Designated States: JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>Without international search report and to be republished upon receipt of that report.</i>

(54) Title: APPARATUS FOR STORING AND MOVING A CASSETTE

## (57) Abstract

A cassette stocker includes a plurality of cassette storage shelves positioned adjacent a cleanroom wall above a cassette docking station, and a cassette mover to carry a cassette between the shelves and the docking station. An interstation transfer apparatus includes an overhead support beam and a transfer arm adapted to carry a cassette between processing stations.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## APPARATUS FOR STORING AND MOVING A CASSETTE

### BACKGROUND OF THE INVENTION

#### Field of the Invention

The present invention relates generally to substrate processing, and more particularly to an apparatus for storing and moving substrate cassettes.

#### Background of the Related Art

Semiconductor devices are made on substrates, such as silicon wafers or glass plates, for use in computers, monitors, and the like. These devices are made by a sequence of fabrication steps, such as thin film deposition, oxidation or nitration, etching, polishing, and thermal and lithographic processing. Although multiple fabrication steps may be performed in a single processing station, substrates must be transported between different processing stations for at least some of the fabrication steps.

Substrates are stored in cassettes for transfer between processing stations and other locations. Although cassettes may be carried manually between processing stations, the transfer of cassettes is typically automated. For example, a cassette may be transported to a processing station in an automatic guided vehicle (AGV), and then loaded from the AGV onto a loading platform in the processing station by a robot. Another robot may extract a substrate from the cassette and transport it into a processing chamber at the processing station. When the fabrication steps are complete, the substrate is loaded back into the cassette. Once all of the substrates have been processed and returned to the cassette, the cassette is removed from the loading platform and transported to another location by the AGV.

In order to ensure that the processing equipment does not sit idle, a nearly continuous supply of unprocessed substrates should be available at the processing station.

Unfortunately, many processing stations can hold only a single cassette at the loading platform. Therefore, once all of the substrates in the cassette have been processed, the

cassette must be quickly replaced, either manually or by an AGV, with a new cassette containing unprocessed substrates. Unfortunately, running such a just-in-time cassette inventory system requires either significant operator oversight or a large number of AGVs, thereby increasing the costs of the fabrication facility.

Therefore, there is a need for a method and apparatus which continuously supplies substrate cassettes to a processing system so that system down time is reduced or eliminated.

## SUMMARY OF THE INVENTION

The present invention provides a method and apparatus for storing multiple cassettes at a processing station, ensuring that a nearly continuous supply of unprocessed substrates is available for processing and that the processing equipment does not sit idle. Multiple cassettes can be stored at a processing station in a front end support frame and a cassette can be moved to a docking station where substrates are extracted and transferred to the processing equipment. An automation system is mounted or otherwise disposed on the frame to transfer cassettes between docking stations or between processing stations. The apparatus does not increase the footprint, *i.e.*, the required area on the cleanroom floor, of the processing station. In another aspect of the invention, cassettes can be transported between different processing stations without the use of an AGV.

In one aspect of the invention, an apparatus is provided which includes a front end frame having one or more substrate transfer stations and multiple cassette storage stations.

An automated transfer assembly is preferably disposed adjacent the transfer stations and the storage stations to move cassettes between the storage stations and the transfer stations. Additionally, an automated transfer assembly can be located between processing stations to transfer cassettes between processing stations without the need for manual or AGV assistance.

In another aspect of the invention, a method is provided for delivering a continuous supply of cassettes to a processing system. The method preferably includes providing at least one transfer station and multiple storage stations and moving cassettes between the

storage stations and the transfer stations to ensure that substrates are continually supplied to the processing system. Additionally, a method is provided for transferring cassettes between processing stations to continue the processing sequence without the need for manual or AGV assistance.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic top view of a processing station according to the present invention.

FIG. 2 is a schematic perspective view of a cassette for holding substrates.

FIG. 3 is a schematic perspective view of a cassette stocker according to the present invention.

FIG. 4A is a schematic front view of the cassette stocker of FIG. 3.

FIG. 4B is a schematic front view of the cassette stocker of FIG. 4A with a plurality of cassettes.

FIG. 5A is a schematic side view of the cassette stocker of FIG. 3.

FIG. 5B is a schematic side view of the cassette stocker of FIG. 5A with a plurality of cassettes.

FIG. 6 is a schematic top view of an end effector located over a docking station.

FIGS. 7A, 7B and 7C are schematic perspective views illustrating the end effector lifting and moving a cassette.

FIGS. 8A and 8B are schematic front views of the cassette stocker illustrating the path the end effector takes in moving a cassette between a loading platform and a cassette docking platform.

FIG. 9 is a schematic front view of two loading and storage stations connected by an interstation transfer mechanism.

FIG. 10 is a schematic perspective view of another embodiment of a cassette stocker according to the present invention.

## DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

In the following description, the term "substrate" broadly covers any object that is being processed in a semiconductor device processing system. The term "substrate" includes, for example, semiconductor wafers, flat panel displays, glass plates or disks, and plastic workpieces.

Figure 1 is a top view of a processing station 20 of the present invention in which one or more substrates 10 are processed. The processing station 20 has a front-end staging area 22 which is separated from a loading and storage area 24 by a cleanroom wall 26. Cleanroom wall 26 separates a cleanroom 28, where loading and storage area 24 is located, from a gray area 30, where a processing system 32 is housed. The loading and storage area 24 is where cassettes of substrates are delivered and loaded/unloaded into/from the processing station 20. Processing system 32 may include one or more load lock chambers 34, a central transfer chamber 36, and a plurality of processing chambers 38. Inside processing chambers 38, the substrate may be subjected to a variety of fabrication steps, such as thin film deposition, oxidation, nitration, etching, thermal processing or lithographic processing. For the purposes of the invention, the processing system and staging area illustrated in Figure 1 are merely representative. The processing system could have just a single processing chamber, or it could be a device, such as a chemical mechanical polisher, that does not include any processing chambers. In addition, the processing system could perform metrology instead of or in addition to the fabrication steps.

Referring to Figure 2, one or more substrates 10 are brought to the loading and storage area 24 of the processing station in a cassette 100. Substrates 10 are supported in cassette 100 in a generally parallel horizontal configuration by slot ridges 102. Substrates may be loaded and unloaded from cassette 100 through an entry port 103 located in a generally flat front face 106 of the cassette. A removable cassette door 104 may be secured in entry port 103 to prevent the substrates from being exposed to contaminants when the cassette is moved between processing stations or stored outside a processing station. Each cassette 100 also includes three cylindrical indentations 108 (shown in phantom and only two of which are visible in Figure 2) formed in an underside 110 of the

cassette. When cassette 100 is stored at the processing station, three support pins will fit into indentations 108 to support the cassette. Two handles 112 (only one is shown in this perspective view) which project from sidewalls 114 may be used to manually carry the cassette. A generally rectangular flange 116 having an L-shaped cross-section projects from a top surface 118 of the cassette. As discussed below, a robotic cassette mover at the processing station may manipulate the cassette by means of flange 116.

Referring to Figures 1 and 3-5B, loading and storage area 24 of processing station 20 includes a cassette loading platform 52, two cassette docking or substrate transfer stations 40 located on either side of loading platform 52, and a cassette stocker or storage stations 50 (only partially illustrated in Figure 1 so that docking stations 40 may be seen) for storing cassettes at the processing station and moving the cassettes to and from loading platform 52 and docking stations 40.

A cassette may be placed onto or removed from loading platform 52 either manually or by an AGV. From the loading platform, the cassette may be moved to one of docking stations 40 or into cassette stocker 50. Loading platform 52 has generally the same perimeter shape as a cassette. Three support pins 54 (only two are seen in the side view of FIG. 5A) project vertically from the loading platform to mate with the indentations in the underside of the cassette to support the cassette on the loading platform.

To transfer substrates through the cleanroom wall, cassettes 100 (shown in phantom in FIG. 1) may be positioned at one or both docking stations 40. Each docking station 40 includes a docking platform 42 to support a cassette, an opening 46 formed through cleanroom wall 26, a movable door 44 which seals opening 46 when a substrate is not to be transferred through opening 46 or a cassette is not positioned on docking platform 42, and a mechanism to unlock cassette door 104 and retract the door into front-end staging area 22 to provide horizontal access to the substrate. A description of docking station 40 may be found in U.S. Patent Application Serial No. 09/012,323, entitled A WAFER CASSETTE LOAD STATION, filed January 23, 1998, by Eric A. Nering, et al., assigned to the assignee of the present invention, the entire disclosure of which is

incorporated herein by reference.

Cassette stocker 50 includes a frame 60 that supports one or more storage racks 58 (not illustrated in FIG. 1 so that the docking stations may be shown), and a robotic cassette mover 56 to move the cassettes between the storage rack, the loading platform, and the docking platforms. Frame 60 may be bolted to the floor of cleanroom 28 and/or secured to the cleanroom wall 26. The frame 60 is at least partially disposed below the docking platforms 42 and loading platform 52 so that the footprint of processing station 20 is not increased.

Storage rack 58 may include a vertical column of support shelves above each of the two docking stations 40. Each column may include, for example, one, two, three or more individual support shelves. Thus, storage rack 58 shown in Figures 3-5b provides storage space for six cassettes 100 in support shelves 62a-62h (see FIG. 4B). Each support shelf, such as support shelf 62a, may be a horizontally oriented plate having substantially the same perimeter shape as the cassette. Three support pins 64 (only two are shown in the side view of FIG. 5A) project vertically from the support shelf and are positioned to mate with receiving indentations 108 in the underside of the cassette. Two vertical posts 66 may be used to secure the outer edge of each support shelf 62a-62h to frame 60. Additionally, the support shelves could be secured to the cleanroom wall for additional support.

Robotic cassette mover 56 is used to move cassettes between the storage shelves, the loading platform and the docking platforms. The robotic cassette mover includes a vertically movable end effector 72 which is attached to a horizontally movable support strut 74. The support strut 74 permits arbitrary horizontal movement of end effector 72 in a plane parallel to cleanroom wall 26. The bottom of support strut 74 may be secured to a lateral slider 76 which can move horizontally along a horizontal guide 78 that is attached to or formed as part of frame 60. The lateral slider 76 may be driven from side-to-side by a horizontal lead screw 80, which is rotated by a horizontal drive motor 82. The horizontal drive motor 82 may be secured to frame 60. Similarly, end effector 72 may be attached to a vertical slider 84 which can slide vertically along a vertical guide 86



attached to or formed as part of support strut 74. The vertical slider 84 may be driven up and down by a vertical lead screw 87 (shown in phantom in FIGS. 4A-5B) which may be rotated by a vertical drive motor 88. The vertical drive motor may be supported by lateral slider 76. Horizontal drive motor 82 and vertical drive motor 88 may be connected to a control system (not shown), such as a programmable digital computer, to control the vertical and horizontal motion of end effector 72. The actuators which drive the movement of the end effector may include stepper motors, pneumatic actuators and other devices known to impart movement in a controllable manner. In addition, a belt drive assembly or other known mechanism can be utilized to drive the sliders both vertically and horizontally.

Referring to FIG. 6, end effector 72 projects horizontally from support strut 74 towards cleanroom wall 26. The end effector includes a generally flat, hook-shaped finger 90 that defines a rectangular gap 92 which is open on one side of the end effector. The end effector is adapted to engage a portion of a cassette through the use of the open end of the end effector.

Referring to FIG. 7A, in order to transport cassette 100, end effector 72 is vertically positioned between flange 116 and top surface 118 of cassette 100. Referring to FIG. 7B, the end effector is moved laterally so that a base 117 of flange 116 fits into gap 92. Finally, referring to FIG. 7C, end effector 72 is moved vertically upwards so that an inner rim 94 of the end effector contacts an underside 119 of flange 116 to lift the cassette. The end effector may then be moved laterally to carry cassette 100 to another support shelf or platform.

Referring to FIG. 8A, a cassette may be transported from loading platform 52 to a support shelf, such as support shelf 62c. With support strut 74 positioned to the side of loading platform 52, a cassette 100 is loaded onto the loading platform, either manually or by an AGV. To lift the cassette off loading platform 52, end effector 72 is positioned to the left of the cassette at a vertical height between upper surface 118 of the cassette and the lower surface of flange 116. The support strut 74 moves rightwardly until end effector 72 engages the support flange (phantom line A). Then, the end effector moves upwardly

to raise the cassette off of the loading platform (phantom line B). To move the cassette to one of the support shelves, e.g., support shelf 62c, end effector 72 raises the cassette until it is generally aligned above the support shelf 62c, with sufficient vertical clearance to permit the underside of the cassette to move horizontally over support pins 64 (phantom line C). Then support strut 74 is moved leftwardly to position the cassette over the support shelf, and the end effector moves downwardly until the cassette rests on support pins 64 (phantom line D). The end effector may be withdrawn by moving it leftwardly until it clears the flange, and then moving it upwardly and rightwardly between the top of the flange and the bottom of support shelf 62b (phantom line E).

Referring to FIG. 8B, in order to remove the cassette from support shelf 62c, these steps are generally repeated in reverse order. Specifically, end effector moves leftwardly between the top of flange 116 and the bottom of support shelf 62b (phantom line F), downwardly until it is located at a vertical position between the top surface of the cassette and the underside of the flange (phantom line G), and rightwardly until it engages the flange (phantom line H). Then the end effector moves upwardly to lift the cassette off the support plate and then rightwardly to carry the cassette into the vertical channel between the storage racks (phantom line I). From this position, the cassette may be moved up or down and then left or right to a new storage shelf, to one of the docking platforms, or to the loading platform.

In the embodiments described in FIGS. 7A-8B, hook-shaped finger 90 of end effector 72 curves to the right so that rectangular gap 92 is open on the right. Of course, if hook-shaped finger 90 curved to the left so that rectangular gap 92 was open on the left, then the relative lateral motion of the end effector to engage and disengage the cassette would be reversed. For example, to lift the cassette from a support shelf, the end effector would be positioned on the right side of the cassette and moved to the leftwardly to engage the flange.

In operation, a cassette 100 is transported to processing station 20 and placed on loading platform 52, e.g., manually or by an AGV. The robotic cassette mover 56 transports the cassette from the loading platform to one of the docking stations, which

aligns the front face of the cassette with docking station door 44, and then retracts docking station door 44 and cassette door 104 so that entry port 103 mates with opening 46 in cleanroom wall 26. A wafer handling robot 48 in front-end staging area 22 extracts the substrates from the cassette through opening 46 and inserts them into one of the load lock chamber 34. A robot 39 in transfer chamber 36 moves substrates between the load lock and the processing chambers. When the fabrication steps are completed, wafer handling robot 48 extracts the substrate from one of the lock load chambers, and returns it to cassette 100 through opening 46. Once all of the substrates have been processed, cassette door 104 is closed, the cassette is moved to storage rack 58 or loading platform 52, and a new cassette containing unprocessed substrates is loading into the docking station.

Referring to FIG. 9, an interstation transfer apparatus 120 may be used to move cassettes between adjacent processing stations 20' and 20", thereby eliminating the need for AGVs or manual transport. Interstation transfer apparatus 120 includes an overhead support beam 122 which may be secured to posts 66' and 66" of adjacent cassette stockers 50' and 50". A transfer arm 124 may be attached to a slider 126 that moves horizontally along a guide 127 that is attached to or formed as part of support beam 122. The slider may be moved horizontally by a lead screw 130 which may be rotated by a horizontal drive motor 132. An end effector 128 may be connected to transfer arm 124 by a pneumatic actuator 134 to provide end effector 128 with a short vertical stroke.

In order to transport the cassettes between adjacent processing stations, the cassette is moved by robotic cassette mover 56' to the upper right-hand support shelf, *i.e.*, support shelf 62e', of cassette stocker 50'. End effector 128 moves horizontally over flange 116, then down to a vertical position between the bottom of the flange and the top of the cassette. Then the end effector moves to the right until it engages the cassette flange. End effector 128 lifts the cassette off support plate 62e', and horizontal drive motor 132 drives the transfer arm rightwardly until the cassette is located over the upper left-hand support shelf 62a" of cassette stocker 50". Finally, the end effector lowers the cassette onto support shelf 62a" and withdraws.

Interstation transfer apparatus 120 provides an extremely simple method of

transferring cassettes between adjacent processing stations. This may be particularly useful where one of the processing stations is a metrology station (which could be located entirely inside the cleanroom), since it permits the metrology measurements to be made without building a metrology apparatus into the processing equipment and without using a factory automation system.

Although cassette stockers 50' and 50" are illustrated as positioned against the same cleanroom wall, the interstation transfer apparatus could include rotary mechanisms to allow handoff between end effectors on different support beams. This would permit processing stations 20' and 20" to be positioned around the corners or at opposite walls of the cleanroom.

The embodiments described above include two storage racks 58 disposed above two docking stations 42 and a loading station 52 disposed between the two docking stations. Preferably, six cassette support shelves 62(a)-(f) are disposed above the two docking stations. While this configuration is believed to provide the highest throughput of substrates in the available space, the invention also includes a single docking station with one or more cassette support shelves disposed in proximity to the docking station. Figure 10 is a perspective view of one embodiment of the invention having a single docking station 42 and three storage shelves 62(a)-(c) disposed above the docking station. Support shelves 62(b)-(c) are shown in phantom to indicate that only one support shelf 62(a) could be used to advantage. Components which form a part of the earlier described embodiments are identified using the same numbers.

Substrates may be loaded into the system at either the docking station position, at any one of the storage shelf positions or at a loading station 52. The loading station 52 could be disposed adjacent either a support shelf or the docking station. The substrate mover system described above in reference to the other embodiments is utilized with the single stack embodiment and operates in the same manner except that support shelves disposed in a single stack eliminate the transfer sequence from the additional stack.

Each of the embodiments described herein utilize available space above docking stations, thereby increasing the storage capability of the system without increasing the

footprint (area occupied by the system measured in terms of floor space) of the system. Accordingly, a processing system could utilize any configuration of the storage device of the present invention including cassette support shelves disposed adjacent a docking station. Preferably, a cassette mover is also disposed in proximity to the support shelves and the docking station to effect transfer of cassettes between the support shelves and the docking stations.

The present invention has been described in terms of a number of embodiments. The invention, however, is not limited to the embodiments depicted and described. Rather, the invention is defined by the claims.

What is claimed is:

1. An apparatus for storing cassettes, comprising:  
a plurality of cassette storage shelves; and  
a cassette mover to carry a cassette between the shelves and a docking station, the cassette mover including a support member positioned in front of the shelves and movable in a path generally parallel to the shelves, and an end effector configured to engage the cassette, the end effector movably connected to the support member.
2. The apparatus of claim 1, wherein the shelves are configured to be positioned adjacent a cleanroom wall.
3. The apparatus of claim 2, wherein one or more of the shelves are positioned above the docking station.
4. The apparatus of claim 1, further comprising a frame supporting the cassette storage shelves and the support member.
5. The apparatus of claim 4, wherein the frame substantially fits below the docking station.
6. The apparatus of claim 1, wherein a lower end of the support member is slidably connected to a frame.
7. The apparatus of claim 6, wherein the end effector is joined to a first slider which slidably engages a first, vertical guide joined to the support member.
8. The apparatus of claim 7, wherein the support member is joined to a second slider which slidably engages a second, horizontal guide joined to the frame.

9. The apparatus of claim 8, further comprising a first lead screw engaging the first slider and a first drive motor to rotate the first lead screw and drive the first slider along the first guide to move the end effector vertically.
10. The apparatus of claim 9, further comprising a second lead screw engaging the second slider and a second drive motor to rotate the second lead screw and drive the second slider along the second guide to move the support member and the end effector horizontally.
11. The apparatus of claim 1, wherein the shelves are arranged in a vertical column above the docking station.
12. The apparatus of claim 1, wherein the end effector includes a hook-shaped finger adapted to engage a bottom surface of a flange on a top of the cassette.
13. The apparatus of claim 1, wherein each shelf includes a plurality of pins that project vertically from the shelf to engage corresponding indentations in the underside of the cassette.
14. An apparatus for storing cassettes, comprising:  
a plurality of cassette storage shelves positioned adjacent a wall above a plurality of cassette docking stations; and  
a cassette mover to carry a cassette between the shelves and the docking stations, the cassette mover including a support member positioned in front of the shelves and movable in a plane parallel to the wall, and an end effector configured to engage the cassette, the end effector slidably connected to the support member.
15. The apparatus of claim 14, wherein the shelves are arranged in a vertical column above each docking station.

16. The apparatus of claim 14, wherein adjacent vertical columns of shelves are separated by a vertical channel, and the cassette mover is configured to transport a cassette to a selected support shelf by moving the cassettes vertically through the channel to position the cassette substantially adjacent and above the selected support shelf, and then horizontally to position the cassette over the selected support shelf.

17. A fabrication system, comprising:

- a first processing station to perform a first fabrication step on a substrate, the first processing station including a first docking station, a first plurality of cassette storage shelves positioned above the first docking station, and a first cassette mover to carry a cassette between the first plurality of shelves and the first docking station;

- a second processing station to perform a second fabrication step on the substrate, the second processing station including a second docking station, a second plurality of cassette storage shelves positioned above the second docking station; and a second cassette mover to carry a cassette between the second plurality of shelves and the second docking station; and

- an interstation cassette mover to transport a cassette between one of the first plurality of shelves and one of the second plurality of shelves.

18. The fabrication system of claim 17, wherein the first processing system performs a first fabrication step.

19. The fabrication system of claim 18, wherein the second processing system is a metrology system.

20. The fabrication system of claim 17, wherein the shelves are arranged in columns above the docking stations, and the interstation cassette mover transports the cassette between a topmost shelf of each of the first and second plurality of shelves.




21. The fabrication system of claim 17, wherein the interstation cassette mover includes a the cassette mover a support member positioned in front of the shelves and movable in a path parallel to a cleanroom wall, and an end effector configured to engage the cassette, the end effector vertically movable relative to the support member.



22. A semiconductor processing station, comprising:  
a processing system to perform a fabrication step on a substrate;  
an interface wall separating the processing system from a cleanroom;  
a docking station located in the cleanroom to support a cassette;  
an opening in the interface wall;  
a wafer transfer robot to transfer the substrate through the opening between the docking station and the processing system;  
a loading platform located in the cleanroom adjacent the docking station; and  
a cassette stocker located in the cleanroom, the cassette stocker including,  
i) a plurality of shelves aligned in a vertical column above the docking station,  
and  
ii) a cassette mover to carry a cassette between the shelves, the loading platform, and the docking station, the cassette mover including a support member positioned in front of the shelves and movable in a path generally parallel to the shelves, and an end effector slidably connected to the support member and configured to engage the cassette.

23. A method of operating a processing station, comprising:  
storing a plurality of cassettes on a plurality of cassette storage shelves adjacent a cleanroom wall above a docking station;  
carrying one of the cassettes to the docking station with a cassette mover;  
removing a substrate from the cassette; and  
returning the cassette to the cassette storage shelves with the cassette mover.


24. An apparatus for storing cassettes, comprising:  
one or more docking stations positionable adjacent a cleanroom wall; and  
one or more cassette storage shelves positionable adjacent the cleanroom wall and  
adjacent the one or more cassette docking stations.
25. The apparatus of claim 24 wherein the one or more cassette storage shelves are  
disposed above the one or more docking stations.
26. The apparatus of claim 25 further comprising a cassette mover disposed adjacent  
the one or more docking stations and the one or more cassette storage shelves.
27. The apparatus of claim 26 wherein the cassette mover comprises a vertical slider  
and a lateral slider.
28. The apparatus of claim 27 further comprising a loading station disposed adjacent  
the one or more docking stations.
29. The apparatus of claim 28 further comprising an enclosure disposed about the one  
or more docking stations, the loading station, and the one or more cassette storage shelves.

*Fig. 1*

*Fig. 2*



*Fig. 3*



*Fig. 4A*




Fig. 4B




Fig. 5A




Fig. 5B

6/11




Fig. 6



7/11




Fig. 7A




Fig. 7B





Fig. 7C



*Fig. 8A*

9/11




Fig. 8B

10/11




Fig. 9

11/11




Fig. 10




**Fig. 1**

Fig. 2






Fig. 3





**Fig. 4A**






Fig. 4B



6/11




Fig. 6

7/11




Fig. 7A




Fig. 7B




Fig. 7C

8/11





Fig. 8A

9/11



**Fig. 8B**

10/11




Fig. 9



11/11




Fig. 10



(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
8 June 2000 (08.06.2000)

PCT

(10) International Publication Number  
**WO 00/33355 A3**

(51) International Patent Classification<sup>7</sup>: H01L 21/00

Forbes Avenue, Santa Clara, CA 95051 (US). BELITSKY, Victor; 1618 Meadowlark Lane, Sunnyvale, CA 94087 (US).

(21) International Application Number: PCT/US99/28086

(22) International Filing Date:  
23 November 1999 (23.11.1999)

(74) Agents: BERNADICOU, Michael, A. et al.; Blakely, Sokoloff, Taylor & Zafman LLP, 7th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025 (US).

(25) Filing Language: English

(81) Designated States (national): JP, KR.

(26) Publication Language: English

(30) Priority Data:  
09/201,737 1 December 1998 (01.12.1998) US

(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

(71) Applicant: APPLIED MATERIALS, INC. [US/US]:  
3050 Bowers Avenue, Santa Clara, CA 95052 (US).

Published:

— With international search report.


— Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

(72) Inventors: PERLOV, Ilya; 183 Plake Avenue, Santa Clara, CA 95051 (US). GANTVARG, Evgueni; 2679

[Continued on next page]

(54) Title: APPARATUS FOR STORING AND MOVING A CASSETTE

(57) Abstract: A cassette stocker includes a plurality of cassette storage shelves positioned adjacent a cleanroom wall above a cassette docking station, and a cassette mover to carry a cassette between the shelves and the docking station. An interstation transfer apparatus includes an overhead support beam and a transfer arm adapted to carry a cassette between processing stations.



WO 00/33355 A3



(88) Date of publication of the international search report:  
4 January 2001

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

DOCKET NO: P2000 0353  
SERIAL NO: \_\_\_\_\_  
APPLICANT: Gregor Rihst  
LERNER AND GREENBERG P.A.  
P.O. BOX 2480  
HOLLYWOOD, FLORIDA 33022  
TEL. (954) 925-1100